


Power Metered 1U PDU, 8 x BS 1363 UK sockets, local display, 13 A UK plug 8 x UK

HSP-PDU-M-UK-1U-8

Power PDU. Outlet and inlet as specified for this code.



POWER METERED

HSP-PDU-M-UK-1U-8 is the Hyperspan Power PDU named above. Inlet, outlets and mounting on this sheet are the published values for this code.

KEY FEATURES

- Matched inlet and outlets
- 1U 19-inch rack mount
- BS 1363 13 A UK plug
- Hyperspan Rack fit

Input	
Characteristic	Value for this SKU
Series	Hyperspan Power Metered
Supply	220-240 V AC, single-phase, 50 Hz
Rated current	13 A
Inlet plug	BS 1363 13 A UK plug
Input cord	Factory-fitted cord
Feed	End feed.
Overcurrent	Resettable input breaker matched to the inlet. Upstream protection stays on the distribution board.

Outlets	
Characteristic	Value for this SKU
Outlet map	8 x BS 1363
C13	None on this code
C19	None on this code
UK 13 A	8
Retention	BS 1363 shutters on the UK outlets
Outlet switching	Outlets are permanently on

Monitoring	
Characteristic	Value for this SKU
Local display	Inlet voltage, current, active power and energy
What is metered	The inlet only. Outlets are not metered individually.
Sensors	One port for an optional temperature probe, ordered separately



Power Metered 1U PDU, 8 x BS 1363 UK sockets, local display, 13 A UK plug 8 x UK

HSP-PDU-M-UK-1U-8

Power PDU. Outlet and inlet as specified for this code.

Network

Characteristic	Value for this SKU
Ethernet	10/100
Browser	Inlet readings and alert thresholds
SNMP	v2c and v3 read of the inlet values
Alerts	Email when the inlet crosses the set threshold

Mechanical

Characteristic	Value for this SKU
Mounting	1U 19-inch rack mount
Finish	Black chassis, HYPERSPAN wordmark
Length	Nominal chassis length follows the outlet count. Confirm the mounting drawing before the cabinet is ordered.
Fits	Hyperspan Rack side channel or 19-inch rails, as named for this code

Environment

Characteristic	Value for this SKU
Operating	0 C to 45 C
Humidity	5% to 95% RH, non-condensing
Location	Indoor rack and comms room

Standards this design follows

Characteristic	Value for this SKU
Outlets	BS 1363
Inlet	BS 1363 plug
Safety intent	Specified against BS EN 62368-1 for ICT equipment
EMC intent	Specified against BS EN 55032

NOTES

HSP-PDU-M-UK-1U-8 is the Hyperspan Power PDU named above. Inlet, outlets and mounting on this sheet are the published values for this code. Confirm the inlet, residual-current protection and distribution-board capacity with the project electrical designer before installation. A management network drop is required for remote reading. Order the temperature probe separately if the sensor port is used. Product warranty; 25-Year System Warranty applies to qualifying registered Hyperspan channels