

Power Sense vertical PDU, 16 x IEC C13 and 2 x IEC C19 locking outlets, inlet display, IEC 60309 16 A blue commando, 3 m cord 16 x C13 + 2 x C19

HSP-PDU-SENSE-V-16C13-2C19-16A

Power Sense. Inlet metering on a 3 m cord.



POWER SENSE

HSP-PDU-SENSE-V-16C13-2C19-16A is a Power Sense monitored vertical PDU. One display and one network reading cover the whole inlet. Outlets are locking IEC sockets and they stay on. The cord is 3 m.

KEY FEATURES

- Inlet display
- Network inlet reading
- Sensor port
- Locking IEC outlets
- 3 m commando cord

Input	
Characteristic	Value for this SKU
Series	Hyperspan Power Sense
Supply	220-240 V AC, single-phase, 50 Hz
Rated current	16 A
Inlet plug	IEC 60309 16 A, 2P+E, blue
Input cord	3 m flexible cord, factory fitted
Feed	End feed.
Overcurrent	Resettable input breaker matched to the inlet. Upstream protection stays on the distribution board.

Power Sense vertical PDU, 16 x IEC C13 and 2 x IEC C19 locking outlets, inlet display, IEC 60309 16 A blue commando, 3 m cord 16 x C13 + 2 x C19

HSP-PDU-SENSE-V-16C13-2C19-16A

Power Sense. Inlet metering on a 3 m cord.

Outlets

Characteristic	Value for this SKU
Outlet map	16 x IEC 60320 C13, 2 x IEC 60320 C19
C13	16
C19	2
UK 13 A	None on this code
Retention	IEC outlets fitted with retention clips
Outlet switching	Outlets are permanently on

Monitoring

Characteristic	Value for this SKU
Local display	Inlet voltage, current, active power and energy
What is metered	The inlet only. Outlets are not metered individually.
Sensors	One port for an optional temperature probe, ordered separately

Network

Characteristic	Value for this SKU
Ethernet	10/100
Browser	Inlet readings and alert thresholds
SNMP	v2c and v3 read of the inlet values
Alerts	Email when the inlet crosses the set threshold

Mechanical

Characteristic	Value for this SKU
Mounting	Vertical 0U in the cabinet side channel
Finish	Black chassis, HYPERSPAN wordmark
Length	Nominal chassis length follows the outlet count. Confirm the mounting drawing before the cabinet is ordered.
Fits	Hyperspan Rack side channel or 19-inch rails, as named for this code

Environment

Characteristic	Value for this SKU
Operating	0 C to 45 C
Humidity	5% to 95% RH, non-condensing
Location	Indoor rack and comms room

Power Sense vertical PDU, 16 x IEC C13 and 2 x IEC C19 locking outlets, inlet display, IEC 60309 16 A blue commando, 3 m cord 16 x C13 + 2 x C19

HSP-PDU-SENSE-V-16C13-2C19-16A

Power Sense. Inlet metering on a 3 m cord.

Standards this design follows

Characteristic	Value for this SKU
Outlets	IEC 60320 for C13 and C19
Inlet	IEC 60309 industrial plug
Safety intent	Specified against BS EN 62368-1 for ICT equipment
EMC intent	Specified against BS EN 55032

NOTES

HSP-PDU-SENSE-V-16C13-2C19-16A is a Power Sense monitored vertical PDU. One display and one network reading cover the whole inlet. Outlets are locking IEC sockets and they stay on. The cord is 3 m.

Confirm the inlet, residual-current protection and distribution-board capacity with the project electrical designer before installation.

A management network drop is required for remote reading. Order the temperature probe separately if the sensor port is used.

Product warranty; 25-Year System Warranty applies to qualifying registered Hyperspan channels