

Power Vertical PDU, 20 x IEC C13 sockets, IEC 60309 16 A blue commando inlet 20 x C13

HSP-PDU-V-C13-20-16A

Power PDU. Outlet and inlet as specified for this code.



POWER BASIC

HSP-PDU-V-C13-20-16A is the Hyperspan Power PDU named above. Inlet, outlets and mounting on this sheet are the published values for this code.

KEY FEATURES

- Matched inlet and outlets
- Vertical 0U in the cabinet side channel
- IEC 60309 16 A, 2P+E, blue
- Hyperspan Rack fit

Input	
Characteristic	Value for this SKU
Series	Hyperspan Power Basic
Supply	220-240 V AC, single-phase, 50 Hz
Rated current	16 A
Inlet plug	IEC 60309 16 A, 2P+E, blue
Input cord	Factory-fitted cord
Feed	End feed.
Overcurrent	Resettable input breaker matched to the inlet. Upstream protection stays on the distribution board.

Power Vertical PDU, 20 x IEC C13 sockets, IEC 60309 16 A blue commando inlet 20 x C13

HSP-PDU-V-C13-20-16A

Power PDU. Outlet and inlet as specified for this code.

Outlets

Characteristic	Value for this SKU
Outlet map	20 x IEC 60320 C13
C13	20
C19	None on this code
UK 13 A	None on this code
Retention	IEC outlets fitted with retention clips
Outlet switching	Outlets are permanently on

Monitoring

Characteristic	Value for this SKU
Metering	No display and no network meter on this code

Network

Characteristic	Value for this SKU
Network	No Ethernet port on this code

Mechanical

Characteristic	Value for this SKU
Mounting	Vertical 0U in the cabinet side channel
Finish	Black chassis, HYPERSPAN wordmark
Length	Nominal chassis length follows the outlet count. Confirm the mounting drawing before the cabinet is ordered.
Fits	Hyperspan Rack side channel or 19-inch rails, as named for this code

Environment

Characteristic	Value for this SKU
Operating	0 C to 45 C
Humidity	5% to 95% RH, non-condensing
Location	Indoor rack and comms room

Standards this design follows

Characteristic	Value for this SKU
Outlets	IEC 60320 for C13 and C19
Inlet	IEC 60309 industrial plug
Safety intent	Specified against BS EN 62368-1 for ICT equipment
EMC intent	Specified against BS EN 55032



Power Vertical PDU, 20 x IEC C13 sockets, IEC 60309 16 A blue commando inlet 20 x C13

HSP-PDU-V-C13-20-16A

Power PDU. Outlet and inlet as specified for this code.

NOTES

HSP-PDU-V-C13-20-16A is the Hyperspan Power PDU named above. Inlet, outlets and mounting on this sheet are the published values for this code.

Confirm the inlet, residual-current protection and distribution-board capacity with the project electrical designer before installation.

This code has no network port.

Product warranty; 25-Year System Warranty applies to qualifying registered Hyperspan channels