


Equipment Cabinet 42U 600 x 800 mm

HSP-RACK-EQ-42U-6080

Rack cabinet. Size, door and load as specified for this code.



PRODUCT OVERVIEW

HSP-RACK-EQ-42U-6080 is a 42U Hyperspan Rack equipment cabinet. The footprint is 600 x 800 mm. The published static load is 800 kg. The front door is solid steel. 19-inch EIA-310 rails, numbered in U, are fitted front and rear. The doors lock, the side panels come off, and the roof has a brush cable entry. It is supplied flat-packed for assembly on site. Baying is supported, and the baying kit is ordered as an accessory. Typical use: Comms rooms / wiring closets. Specify it with Power PDUs, Rack panels and Hyperband fibre as a Hyper House bill of materials.

KEY FEATURES

- 42U of 19-inch mounting
- 800 kg static load
- Numbered EIA-310 rails, front and rear
- Roof brush cable entry
- Supplied flat-packed for site assembly
- 600 x 800 mm footprint
- Solid steel front door
- Lockable doors and removable side panels
- Black powder-coated steel
- Baying supported. Order the baying kit separately.

Characteristic	Value for this SKU
Product code	HSP-RACK-EQ-42U-6080
Cabinet	Equipment
Rack units	42U
Footprint	600 x 800 mm
Width	600 mm
Depth	800 mm
Static load	800 kg static
Mounting	19-inch EIA-310
Rails	Front and rear, numbered in U
Front door	Solid steel
Rear door	Lockable steel
Side panels	Removable
Roof	Brush cable entry
Material	Steel
Finish	Black powder coat
Supply	Flat-packed
Baying	Supported. Order the baying kit separately.
Application	Comms rooms / wiring closets
Warranty	Product warranty; 25-Year System Warranty applies to qualifying registered Hyperspan channels



Equipment Cabinet 42U 600 x 800 mm

HSP-RACK-EQ-42U-6080

Rack cabinet. Size, door and load as specified for this code.

NOTES


It is supplied flat-packed for assembly on site. The assembly manual for this code shows the exploded diagram and the build sequence.

19-inch EIA-310 rails accept Hyperspan patch panels, fibre panels, Power PDUs and Manage cable managers.

Baying kits, plinths, castors, fan trays and the earth bonding kit are accessories, ordered separately.

Product warranty; 25-Year System Warranty applies to qualifying registered Hyperspan channels

EXPLODED ASSEMBLY



Schematic. Numbers match the parts list.