



Engineered for long-distance, high-power performance, we can deliver:

Product Code: HSP-TERM-C5E-KJ

Cat5e


- Cat5e 23AWG Solid Copper
- U/UTP No Overall Screening
- No Conductor Screening
- Outer Sheath Colour White
- Reaction-to-fire class EN 13501-6 NPD
- Smoke development class EN13501-6 NPD
- Fixed Building Installation

Product Overview

Cat5e Keystone Jack. Hyperspan TERMINATE product for structured copper infrastructure. Confirm final availability and certified documentation with Hyperspan Technical Support for live projects.

Each cable consists of 8 colour-coded solid oxygen-free copper conductors, arranged into four balanced twisted pairs. Construction: U/UTP. Overall screening: None. Conductor screening: None.

The cable is finished with a LSZH outer sheath (White) and is intended for structured cabling installations where the declared reaction-to-fire performance NPD is required.



HYPERSPAN  
CAT5e · WHITE  
0cø LSZH · Solid copper · Optional colourway

Engineered for long-distance, high-power performance, we can deliver:

Product Code: HSP-TERM-C5E-KJ

Cat5e

PRODUCT SPECIFICATION

| Characteristic                  | Value                                   |
|---------------------------------|-----------------------------------------|
| Conductor Surface               | Bare copper                             |
| Conductor Material              | 99.99% Oxygen-Free Copper               |
| AWG Size                        | 23 AWG                                  |
| Conductor Category              | Class 1 – Solid                         |
| Total Number of Cores           | 8                                       |
| Stranding Element               | Twisted pairs                           |
| Core Insulation                 | High-density polyethylene (HDPE)        |
| Cable Construction              | U/UTP                                   |
| Overall Screening               | None                                    |
| Conductor Screening             | None                                    |
| Outer Sheath Material           | LSZH                                    |
| Outer Sheath Colour             | White                                   |
| Packaging                       | 500m                                    |
| Flame Retardant (IEC 60332-1-2) | yes                                     |
| Reaction-to-Fire (EN 13501-6)   | NPD                                     |
| Smoke Development (EN 13501-6)  | NPD                                     |
| Flaming Droplets (EN 13501-6)   | NPD                                     |
| Acidity (EN 13501-6)            | NPD                                     |
| Outer Diameter (approx.)        | ca. 6.1–7.5 mm (construction dependent) |
| Installation Temperature Range  | -10°C to +60°C                          |
| Operating Temperature Range     | -20°C to +75°C                          |
| NVP                             | 69 %                                    |
| Application                     | —                                       |
| Warranty                        | 25-Year System Warranty                 |

Engineered for long-distance, high-power performance, we can deliver:

Product Code: HSP-TERM-C5E-KJ

Cat5e

Standards

| Applicable Standards  | Subject                                                                 |
|-----------------------|-------------------------------------------------------------------------|
| ISO/IEC 11801         | Information technology — Generic cabling for customer premises          |
| EN 50173-1            | Information technology — Generic cabling systems                        |
| ANSI/TIA-568.2-D      | Balanced twisted-pair telecommunications cabling                        |
| EN 50575:2014+A1:2016 | Power, control and communication cables — reaction to fire              |
| EN 13501-6            | Fire classification of construction products — cables                   |
| EN 50399              | Common test methods for cables under fire conditions                    |
| EN 60332-1-2          | Tests on electric and optical fibre cables under fire conditions        |
| EN 61034-2            | Measurement of smoke density of cables burning under defined conditions |
| EN 60754-2            | Test on gases evolved during combustion of materials from cables        |

| Environmental & Compliance Certifications |                                                     |
|-------------------------------------------|-----------------------------------------------------|
| RoHS-II / RoHS-III                        | Compliant — hazardous substance restrictions        |
| WFD / SCIP                                | Support for substance information where applicable  |
| POPs (EU)                                 | Persistent organic pollutants requirements observed |
| CE / UKCA                                 | Conformity marking as applicable to intended market |
| Declared CPR class                        | NPD                                                 |
| DoP reference                             | HSP-DOP-TERM-C5E-KJ                                 |

Power, control and communication cables — cables for general applications in construction works subject to reaction-to-fire requirements. Confirm the certified Declaration of Performance revision with Hyperspan Technical Support before procurement or installation.